



| SAB 18/988 | | | | | | | | | | | | | | | | | | | | | | |
|--|------------|------------------------------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Veiligheidsklasse 2 | | | | | | | | | | | | | | | | | | | | | | |
| Maximale permanente belasting in kN/m ² | | | | | | | | | | | | | | | | | | | | | | |
| bij 0,56 kN/m ² sneeuw of 1,00 kN/m ² over 10 m ² | | | | | | | | | | | | | | | | | | | | | | |
| Aantal velden | Dikte (mm) | Gewicht (kg/m ²) | Overspanning (m) | | | | | | | | | | | | | | | | | | | |
| | | | 1,00 | 1,25 | 1,50 | 1,75 | 2,00 | 2,25 | 2,50 | 2,75 | 3,00 | 3,25 | 3,50 | 3,75 | 4,00 | 4,25 | 4,50 | 4,75 | 5,00 | 5,25 | 5,50 | 5,75 |
| ▲▲▲ | 0,63 | 6,26 | 0,58 | | | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 0,99 | 0,01 | | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 1,30 | 0,16 | | | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 1,71 | 0,37 | | | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 2,10 | 0,57 | | | | | | | | | | | | | | | | | | |
| ▲▲▲▲ | 0,63 | 6,26 | 2,88 | 0,97 | 0,13 | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 3,89 | 1,48 | 0,43 | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 4,65 | 1,87 | 0,65 | 0,03 | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 5,68 | 2,39 | 0,95 | 0,22 | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 6,64 | 2,88 | 1,23 | 0,40 | | | | | | | | | | | | | | | | |
| ▲▲▲▲▲ | 0,63 | 6,26 | 2,02 | 0,53 | | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 2,81 | 0,93 | 0,11 | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 3,41 | 1,23 | 0,28 | | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 4,21 | 1,64 | 0,51 | | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 4,96 | 2,01 | 0,73 | 0,08 | | | | | | | | | | | | | | | | |



| SAB 18/988 | | | | | | | | | | | | | | | | | | | | | | |
|--|------------|------------------------------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| Veiligheidsklasse 3 | | | | | | | | | | | | | | | | | | | | | | |
| Maximale permanente belasting in kN/m ² | | | | | | | | | | | | | | | | | | | | | | |
| bij 0,56 kN/m ² sneeuw of 1,00 kN/m ² over 10 m ² | | | | | | | | | | | | | | | | | | | | | | |
| Aantal velden | Dikte (mm) | Gewicht (kg/m ²) | Overspanning (m) | | | | | | | | | | | | | | | | | | | |
| | | | 1,00 | 1,25 | 1,50 | 1,75 | 2,00 | 2,25 | 2,50 | 2,75 | 3,00 | 3,25 | 3,50 | 3,75 | 4,00 | 4,25 | 4,50 | 4,75 | 5,00 | 5,25 | 5,50 | 5,75 |
| ▲▲▲ | 0,63 | 6,26 | 0,58 | | | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 0,99 | 0,01 | | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 1,30 | 0,16 | | | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 1,71 | 0,37 | | | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 2,10 | 0,57 | | | | | | | | | | | | | | | | | | |
| ▲▲▲▲ | 0,63 | 6,26 | 2,88 | 0,97 | 0,13 | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 3,89 | 1,48 | 0,43 | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 4,65 | 1,87 | 0,65 | 0,03 | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 5,68 | 2,39 | 0,95 | 0,22 | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 6,64 | 2,88 | 1,23 | 0,40 | | | | | | | | | | | | | | | | |
| ▲▲▲▲▲ | 0,63 | 6,26 | 2,02 | 0,53 | | | | | | | | | | | | | | | | | | |
| | 0,70 | 6,95 | 2,81 | 0,93 | 0,11 | | | | | | | | | | | | | | | | | |
| | 0,75 | 7,45 | 3,41 | 1,23 | 0,28 | | | | | | | | | | | | | | | | | |
| | 0,88 | 8,74 | 4,21 | 1,64 | 0,51 | | | | | | | | | | | | | | | | | |
| | 1,00 | 9,93 | 4,96 | 2,01 | 0,73 | 0,08 | | | | | | | | | | | | | | | | |



- In de tabel is rekening gehouden met de standaard veranderlijke belasting volgens NEN 6702
- Naast de weergegeven neerwaartsebelasting is minimaal nog 0,85 kN/m² aan opwaartse belasting (windzuiging) mogelijk
- Belastingen zijn berekend bij een oplegging van 60 mm en een maximale doorbuiging van L/250